

MAN TGX 18.440 4X2 BLS

SH03261223



Price **9,990 EUR** (net)
12,088 EUR (gross)
 Offer Date 16.08.2025

Body type	Tractor unit
1st reg.	03/2015
Power	324kW (441 HP)
Mileage	814823 km
Storage location	Otopeni - MHS Truck Service

BASIC DATA

Brand	MAN
Model serie	TGX
Model variant	TGX TG2
Body type	Tractor unit (Standard)
Colours	white
Driver's cab	XXL
Berths	2 berths

TECHNICAL DATA

Power	324 kW (441 HP)
Fuel	Diesel
Gearbox type	Semiautomatic
Wheel drive	4x2
Suspension	Leaf air suspension
Axles	2 axles

WEIGHTS AND MEASURES

GVW	18,000 kg
Rear overhang	800 mm
Wheel base	3600 mm
Fuel tank	AdBlue: 60 l Fuel tank: 450 l Fuel tank: 580 l
Emission category	Euro6

EQUIPMENT

Safety

- Antilock Braking System ABS
- Anti Slip Regulation ASR
- Electr. Stability Programm ESP
- Immobilizer
- Rear underrun
- Kerb mirror: right
- Heated wide angle mirror

Comfort

- Adjustable steering column
- Electric window lift 2x
- Automatic climate control
- Driver's armrest
- Electr. lifting sunroof
- Comfortable driver seat
- Additional heating
- Central locking with remote control
- Air-suspended driver seat
- Stationary air conditioning
- Isolated driver's cab
- DC/AC converter

Interior

- Board computer
- Multifunctional steering wheel
- Digital tachograph
- Carpet floor covering
- Cooling box

Exterior

- Self-levelling suspension
- Electr. and heated rear view mirrors
- Low noise
- Rear differential lock
- Fifth wheel

Audio & communication

- Radio/CD

Assistance systems

- Cruise control
- MAN BrakeMatic
- Hill Hold Control HHC
- Speed limiter

Light and sight

- Tinted glass
- Headlight range control
- Daytime running lights

Equipment packages

- Aero package

Wheels and tyres

■ Spare wheel carrier

Others

■ front springs parabolic 7.5 t, rear air suspension 13 t, hub reduction rear axle Hypoid HY-1350, HY axle ratio i 2.71, fuel filter heating, cab insulation NORDIC, wiring for tank truck to ADR, ADR Typ AT, equipment for dangerous goods to ADR, type OX, supply kit for semitrailer with lifting axle or moving-off aid, trailer socket 24V (7-7-pin), pick-up plate 40 mm