

MAN TGX 18.470 4X2 BLS

SH02501025



Body type	Tractor unit
1st reg.	09/2020
Power	346kW (470 HP)
Mileage	456736 km
Storage location	Otopeni - MHS Truck Service

BASIC DATA

Brand	MAN
Model serie	TGX
Model variant	TGX TG2
Body type	Tractor unit (Standard)
Colours	red
Driver's cab	XLX
Berths	2 berths

TECHNICAL DATA

Power	346 kW (470 HP)
Fuel	Diesel
Gearbox type	Automatic
Wheel drive	4x2
Suspension	Leaf air suspension
Axles	2 axles

WEIGHTS AND MEASURES

GVW	18,000 kg
Rear overhang	800 mm
Wheel base	3600 mm
Fuel tank	AdBlue: 60 l Fuel tank: 580 l Fuel tank: 580 l
Emission category	Euro6

EQUIPMENT

Safety

- Antilock Braking System ABS
- Anti Slip Regulation ASR
- Electr. Stability Programm ESP
- Immobilizer
- Retarder
- Rear underrun
- Kerb mirror: right
- Heated wide angle mirror

Interior

- Board computer
- Multifunctional steering wheel
- Aluminum inlays
- CB radio
- Digital tachograph
- Carpet floor covering
- Cooling box

Audio & communication

- Radio
- Mobile phone preparation Bluetooth
- AUX & USB connector

Exterior

- Electr. and heated rear view mirrors
- Low noise
- Rear differential lock
- Fifth wheel

Comfort

- Adjustable steering column
- Electric window lift 2x
- Automatic climate control
- Driver's armrest
- Comfortable driver seat
- Additional heating
- Central locking with remote control
- Air-suspended driver seat
- Cup holder front
- Isolated driver's cab
- DC/AC converter

Light and sight

- Fog lights
- Tinted glass
- Headlight range control
- Cornering light
- LED daytime running lights

Assistance systems

- Efficientcruise
- MAN BrakeMatic
- Brake assist
- Lane-Guard-System LGS
- Hill Hold Control HHC
- Speed limiter

- 1x15 pin plug
- Cab Suspension
- Axle load indicator
- Lifting roof (manual)
- Information and service system
- RIO Box

Wheels and tyres

- Spare wheel carrier

Equipment packages

- Aero package
- Efficientline 3 package
- Safety plus package

Others

- front springs parabolic 7.5 t, rear air suspension 13 t, hub reduction rear axle Hypoid HY-1350, hypoid axle ratio i 2.53, cab insulation NORDIC, trailer socket 24V (15-pin)